



# Sinterit LISA PRO

Product specification



## Benchtop SLS 3D printer

- bigger print volume
- built-in nitrogen chamber
- compatible with many materials
- a possibility of using 3rd party powders
- no calibration needed after delivery

## GENERAL

Technology	SLS
Laser system	IR Laser Diode 5 [W] ; $\lambda = 808$ [nm]
Dimensions	690 x 500 x 880 [mm] (27.1 x 19.7 x 34.6 [in])
Weight	90.0 [kg] (198 [lbs])

## PRINT VOLUME

Max size of print diagonally <sup>1</sup>	PA - 301 [mm] (11.8 [in]) TPU / TPE - 313 [mm] (12.3 [in])
High accuracy max print volume	PA - 110 x 160 x 230 [mm] (4.3 x 6.3 x 9 [in]) TPU / TPE - 110 x 160 x 245 [mm] (4.3 x 6.3 x 9.6 [in])

## PRINTER PARAMETERS

Size of Print Bed	150 x 200 x 260 [mm] (5.9 x 7.9 x 10.2 [in])
XY accuracy	from 0.05 [mm] (0.002 [in])
The layer height Z (min - max)	0.075 - 0.175 [mm] (0.003 - 0.007 [in])

## PRINT FEATURES

Min. wall thickness	from 0.4 [mm] (0.015 [in])
Min. detail size	from 0.1 [mm] (0.004 [in])
Hole Diameter	from 0.5 [mm] (0.020 [in])
Moving Part Clearance	from 0.2 [mm] (0.008 [in])

Information provided within this document are typical values for reference and comparison only. Parameters presented in this data sheet are subject to change. Final part properties may vary based on printed part design and print orientation. Material during tests - parameters are subject to change.



## ADDITIONAL PRINTER FEATURES

Nitrogen chamber	Built-in
Coupling installed in Lisa Pro	Pneumatic quick-coupling Male Plug Nipple DN7.2
Average Nitrogen consumption	0.48 [m <sup>3</sup> /hour]

## SOFTWARE

Software <sup>2</sup>	Sinterit Studio 2019 Open
Supported file types	STL, OBJ, 3DS, FBX, DAE, 3MF
OS compatibility	Microsoft Windows

## COMMUNICATION

LCD screen	Capacitive, color
Touchscreen	7 [in]
On-board camera	Built-in
Connectivity	Wifi, USB port

## HEATING SYSTEM

Independent	Heated: piston, cylinder, Feed bed, Print bed
Max. temperature in the chamber	200 [°C] / 392 [°F]

## POWER

Operating Voltage	220-240 [V] AC, 50/60 [Hz], 7 [A] or 100-130 [V] AC, 50/60 [Hz], 15 [A]
Average power consumption	1.1 [kW]
Maximum power consumption	1.9 [kW]

## PACKAGING

For the transportation of a printer we use dedicated protective packaging. Ask for more information.

Size of package	725 x 635 x 1020 [mm] (28.5 x 25.0 x 40.2 [in])
Package weight	117 [kg] (257.9 [lbs])

## WARRANTY

One year limited warranty

## SOFTWARE VERSIONS

Supported materials	Sinterit Studio OPEN	Sinterit Studio ADVANCED
PA12 Smooth	✓	✓
PA11 Onyx	✓ Inert gas required	✓ Inert gas required
PA11 ESD	-	✓ Inert gas required
Flexa Grey	✓	✓
Flexa Soft	-	✓
Flexa Bright	-	✓
TPE	-	✓
Open Parameters	✓	✓

<sup>1</sup> Max size of print diagonally depends on the type of material.

<sup>2</sup> Technical requirements to install Sinterit Studio Software: Windows 7 or higher / Minimum 500 MB of disc space / Minimum 2 GB of RAM / Graphics adapter compatible with OpenGL 3.0 or higher.